


Gewuchtet G = 6,3 15.000 U/min.
Balanced G = 6,3 15.000 U/min.

Kombi-Fräseraufsteckdorne MAS BT
Combination shell mill adaptors MAS BT

Größe / Size	D mm	A mm	L mm	L1 mm	Art.-Nr. / Order no.	EUR
BT 40	16	55	27	17	● 13-7361-40-16	48,50
BT 40	22	55	32	19	● 13-7361-40-22	48,50
BT 40	27	55	33	21	● 13-7361-40-27	48,50
BT 40	32	60	38	24	● 13-7361-40-32	49,80
BT 40	40	60	41	27	● 13-7361-40-40	55,10
BT 50	16	70	27	17	● 13-7361-50-16	70,10
BT 50	22	70	31	19	● 13-7361-50-22	70,10
BT 50	27	70	33	21	● 13-7361-50-27	70,10
BT 50	32	70	38	24	● 13-7361-50-32	73,40
BT 50	40	70	41	27	● 13-7361-50-40	80,60
BT 50	50	70	45	30	● 13-7361-50-50*	118,70

* Ungewuchtet
* Unbalanced

Messerkopf-Aufnahmen MAS BT
Face mill holders MAS BT



Gewuchtet G = 6,3 15.000 U/min.
Balanced G = 6,3 15.000 U/min.

Größe / Size	D mm	A mm	L1 mm	Art.-Nr. / Order no.	EUR
BT 40	16	40	17	● 13-7388-40-16	40,60
BT 40	16	100	17	▶ 13-7388-40-16-100	42,00
BT 40	22	45	19	● 13-7388-40-22	40,60
BT 40	22	100	19	▶ 13-7388-40-22-100	42,00
BT 40	27	40	21	● 13-7388-40-27	40,60
BT 40	27	100	21	▶ 13-7388-40-27-100	42,00
BT 40	32	50	24	● 13-7388-40-32	57,70
BT 40	32	100	24	▶ 13-7388-40-32-100	57,70
BT 40	40	50	27	● 13-7388-40-40	62,80
BT 40	40	100	27	▶ 13-7388-40-40-100	78,70
BT 50	22	40	19	● 13-7388-50-22	70,40
BT 50	22	100	19	▶ 13-7388-50-22-100	71,60
BT 50	27	40	21	● 13-7388-50-27	70,40
BT 50	27	100	21	▶ 13-7388-50-27-100	71,60
BT 50	32	50	24	● 13-7388-50-32	73,40
BT 50	32	100	24	▶ 13-7388-50-32-100	70,40
BT 50	40	50	27	● 13-7388-50-40	77,10
BT 50	40	100	27	▶ 13-7388-50-40-100	82,30
BT 50	50	78	30	● 13-7388-50-50*	124,60

* Ungewuchtet
* Unbalanced